

FlexPackPRO[®]

XT SERIES TTO



RUGGED

- Built with 7000 series aircraft-grade treated aluminum alloy and stainless steel.
- Vertically-integrated parts manufacturing to ensure quality control and precision assembly.
- Heavy-duty installation brackets and rollers crafted in-house to customer specifications.
- Robust long-life mechanical design requiring zero preventative maintenance.

RELIABLE

- Clutchless ribbon drive and tension control design maximize uptime and long-term performance.
- Superior Festo[®] pneumatics assure image quality control & longer printhead life.
- Precision printhead assembly requires lower air pressure to achieve highest print quality.
- 300dpi Kyocera[®] printheads on self-leveling mounts provide superior code quality through every run.



EXTRA LARGE RIBBON CAPACITY, HOLDS UP TO 3,280' ROLL.



VALUE

- Stainless steel 7" touchscreen controllers come standard with all models.
- ProCode[™] Professional coding design software comes free with all systems.
- Reasonably-priced ribbons, parts and service provide the industry's lowest total cost of ownership.
- On average, complete FlexPackPRO systems list for 25-40% lower than competitive TTO systems of comparable quality.

FlexPackPRO[®]

Thermal Transfer Overprinting

XT SERIES

| Models: | 130iXT / 130cXT | 210iXT / 210cXT / 210cXTL | 420iXT / 420cXT / 420cXTL |
|--|---|--|---|
| Printer Mode: | Intermittent / Continuous | Intermittent / Continuous / Continuous | Intermittent / Continuous / Continuous |
| Maximum Print Area (Width x Length): | 32 mm x 76 mm / 125 mm (1.3" x 3" / 5") | 53 mm x 76 mm / 125 mm / 250 mm (2.1" x 3" / 5" / 10") | 107 mm x 76 mm / 125 mm / 250 mm (4.2" x 3" / 5" / 10") |
| Print Resolution: | 300 dpi | 300 dpi | 300 dpi |
| Max Print Speed: | 400 mm/s / 600mm/s (15.7 in/s / 23.6 in/s) | 450 mm/s / 800mm/s / 800mm (17.7 in/s / 31.5 in/s / 31.5 in/s) | 400 mm/s / 600mm/s (15.8 in/s / 23.6 in/s) |
| Print Gap: | 0.5 mm (0.02") | 0.5 mm (0.02") | 0.5 mm (0.02") |
| Standard Ribbon Width: | 35mm (1.4") | 55mm (2.2") | 110mm (4.3") |
| Maximum Ribbon Length: | 1,000 m (3,280') | 1,000 m (3,280') | 1,000 m (3,280') |
| Ribbon Saver Features: | Yes | Yes | Yes |
| Ribbon Loading: | Integrated Cassette | Integrated Cassette | Integrated Cassette |
| Standard User Interface: | 7" Color Touchscreen (stainless) | 7" Color Touchscreen (stainless) | 7" Color Touchscreen (stainless) |
| Software: | ProCode™ Professional | ProCode™ Professional | ProCode™ Professional |
| Barcodes: | All | All | All |
| Standard Communication: | USB, Ethernet, RS232 | USB, Ethernet, RS232 | USB, Ethernet, RS232 |
| Printer Dimensions (Height x Width x Depth): | 180 mm x 265 mm x 240 mm (7.09" x 10.43" x 9.45") | 180 mm x 265 mm x 250 mm (7.09" x 10.43" x 9.84") | 180 mm x 265 mm x 305 mm (7.09" x 10.43" x 12.01") |
| Printer Weight: | 10 kg (22 lbs) | 11 kg (24 lbs) | 13 kg (27 lbs) |
| Power Supply: | 110 - 120 / 200 - 240 VAC, 50 / 60 Hz | 110 - 120 / 200 - 240 VAC, 50 / 60 Hz | 110 - 120 / 200 - 240 VAC, 50 / 60 Hz |
| Air Supply: | 3 bar / 44 psi (max) | 3 bar / 44 psi (max) | 3 bar / 44 psi (max) |
| Operating Temperature: | 5° - 50° C (41° - 122° F) | 5° - 50° C (41° - 122° F) | 5° - 50° C (41° - 122° F) |

FlexPackPRO[®]

Thermal Transfer Overprinting

CORPORATE LOCATIONS
 GEORGIA | ILLINOIS | NEW JERSEY

(800) 758-9219
gopro@flexpackpro.com
www.flexpackpro.com



901-J South Bolmar Street - West Chester, PA 19382
Phone: (610) 692-2455
sales@elmarkpkg.com
www.elmarkpkg.com